




IP67 CE

+50° -20°



- Corpo in metacrilato o vetro borosilicato
- Tubo lampade tipo Dulux o lineari T8 (solo 18-36-58W) *
- Accensione immediata senza sfarfallii
- Angolo diffusione luminosa 180°
- Temperatura colore 4000° K
- Chiusure laterali a tenuta stagna IP67
- Vita operativa 50'000 h a 20°C

- *Methacrylate or borosilicate glass body*
- *Dulux or Linear T8 lamp type (only 18-36-58W) **
- *Instant ignition, no fluttering*
- *Light diffusion angle 180°*
- *Color temperature 4000° K*
- *Airtight IP67 side locks*
- *Lifespan 50'000 hrs at 20°C*

BDM - Ø 70 mm (Dulux)

metacrilato <i>methacrylate**</i>	potenza <i>power</i>	tensione <i>voltage</i>	flusso luminoso <i>luminous flux</i>	lunghezza zona luce <i>light area length</i>	lunghezza (L) <i>length (L)</i>
	W	V	Lm	mm	Mm
BDMM18240	18	24Vac-dc	1200	240	505
BDMM24240	24	24Vac-dc	1800	340	605
BDMM36240	36	24Vac-dc	2900	435	700
BDMM55240	55	24Vac-dc	4800	560	825
BDMM18220	18	230Vac-dc	1200	240	505
BDMM24220	24	230Vac-dc	1800	340	605
BDMM36220	36	230Vac-dc	2900	435	700
BDMM55220	55	230Vac-dc	4800	560	825

* Aggiungere la lettera "L" al termine del codice prodotto per ordinare la versione lineare T8 - Add "L" at the end of product code to order linear T8 version

** Per la versione con corpo in vetro borosilicato, il codice del prodotto cambia in BDMB - For borosilicate glass version, product code changes in BDMB

ACCESSORI DI FISSAGGIO - *Mounting Accessories*

STD1	staffa angolare corta <i>angular short bracket</i>	Staffa in acciaio zincato con dispositivo di serraggio a vite. La parte a contatto con il tubo è ricoperta di gomma per ammortizzare eventuali vibrazioni delle macchine sulle quali la lampada è installata ed è resistente agli oli, acidi e solventi industriali. <i>Galvanized supporting bracket with clamping screw device. The side in contact with the lamp tube is covered by a rubber band, in order to cushion any vibrations generated by the machine on which the lamp is installed. Resistant to oils, industrial acids and solvents.</i>
STD2	staffa angolare lunga <i>angular long bracket</i>	
STD3	staffa dritta <i>straight bracket</i>	
CLC60 CLC50	collare di sostegno in nylon <i>nylon support bracket</i>	Collare di fissaggio in poliammide PA12, disponibile in due diametri (50 e 60mm). Eccellente resistenza chimica ad acidi inorganici e soluzioni alcaline, limitata resistenza ad acetone, acidi organici, benzene e olio diesel. <i>Fixing collar made of PA12 polyamide. Excellent chemical resistance to inorganic acids and alkaline solutions, limited resistance to acetone, benzene, organic acids and diesel oil.</i>

STD1



STD2



STD3



CLC-50/60

